

# PRODUCT OVERVIEW : Coatings

**STAUF®**

ADHESIVES SINCE 1928

## CRACK FILLER CCF40

FAST HARDENING CONCRETE CRACK FILLER



Permanently closes cracks in sub floors  
Install metal anchor in concrete  
Repair concrete or stone stairs

Quick drying  
For use under any flooring  
Extreme sheer strength

### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Cured Leveling Compounds, Radiant Heated Sub Floors, Metal Floors, Asphalt, Wet Concrete Slab up to 25#/24hrs/1,000SF and 100% RH, Cutback residues (grinded, tested negative for asbestos), Epoxy Sealers (100% solid, cured)

### Cure Time Before Flooring Installation

Approx. 30 minutes

### Packaging Size

10 fl. oz. Plastic Bottle; 5 Part A + 5 Part B per case

### Shelf Life

12 months in original, unopened container

## DYNAMIC JOINT FILLER DJF60

PERMANENTLY FLEXIBLE JOINT FILLER



Fills dynamic joints between slabs  
Remains permanently flexible  
Quick setting, cures within 1 hour

LEED qualified  
Contains no isocyanates  
Contains no solvents  
High shear strength  
Freeze/Thaw stable  
Very low odor  
Extremely fast cure

### Approved Sub Floors

Concrete Slabs, OSB (underlayment grade), Plywood (underlayment grade), Asphalt, Wet Concrete Slab up to 25#/24hrs/1,000 SF and 100% RH

### Approved Trowels/Spread Rate

1/2" x 1/2": up to 77 LF/gal

### Cure Time Until Normal Traffic

Approx. 1 hour

### Packaging Size

1 qt. Refill - 6 count case  
1 gal. Refill - 6 count case

### Mixing Ratio

1 bottle curing agent to 1 container of filler

### Shelf Life

6 months in original, unopened container

## HYDRO-SEAL EHS265

2 COMPONENT EPOXY PRIMER



For use under ULC-500  
Superb penetration of sub floors  
Increases bond of subsequent urethane levelers

Suitable over high moisture slabs  
Quick drying  
Deep penetration of porous floor  
Excellent bond to non-porous floors

### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Wet Concrete Slab up to 25#/24hrs/1000SF and 100% RH, Stained Concretes (well bonded)

### Approved Trowels/Spread Rate

3/8" Nap Roller up to 320 SF/gal.

### Drying Time

Approx. 2 hours or until clear

### Packaging Size

2 1/2 gal. metal combo pail (A + B)  
60 per pallet

### Shelf Life

24 months in original, unopened container

## ISOLATOR ECP280

EPOXY PRIMER



Oil Barrier Over Concrete

Encapsulates oil residues in concrete  
Can be used under any urethane levelers  
Can be used under epoxy and urethane coatings  
Can be used under urethane adhesives

### Approved Sub Floors

Concrete Slabs

### Approved Trowels/Spread Rate

3/8" Nap Roller: up to 100 SF/gal

### Drying Time

Approx. 4 hours

### Packaging Size

1.2 gal Metal Pail Part A + 1.2 qt Metal Can Part B

### Shelf Life

24 months in original, unopened container

## LEVEL-SEAL ULC500

2 COMPONENT SELF-LEVELING COMPOUND



Will withstand any moisture  
Moisture barrier up to 18# or 97% RH  
Applied in any thickness over 1/32"  
Cures in under 4 hours

2 part urethane  
LEED qualified  
No water/solvents/VOC  
Freeze/thaw stable  
Long open time  
Suitable for radiant heat systems  
Bridges Cracks

### Approved Sub Floors

Concrete Slabs, OSB, Plywood, Vinyl, Ceramic Tiles, Stone, Terrazzo, Radiant Heated Sub Floors, Cured Leveling Compounds, Wet Concrete Slab up to 18#/24hrs/1,000SF and 97% RH, Metal Floors, Asphalt

### Thickness

1/32" to 5"

### Approved Trowels/Spread Rate

XBL11 (1/8" x 5/32") up to 42 SF/gal.

### Drying Time

Approx. 4 hours

### Packaging Size

2 gal. plastic pail + 1-3/4 qt. plastic can  
48 per pallet

### Shelf Life

24 months in original, unopened container

# PRODUCT OVERVIEW : Coatings

**STAUF®**

ADHESIVES SINCE 1928

## ARIA PRO CCI600

2 COMPONENT EPOXY BASE COAT



### Epoxy Coating Base Coat

Special formulation for thicker coats  
Can be tinted and/or flaked  
Can be mixed with metallics

#### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Cured Leveling Compounds, Radiant Heated Sub Floors, Drywall, Plaster, Stained Concretes (well bonded)

#### Approved Trowels/Spread Rate

XBL11 (1/8" x 5/32") up to 42 SF/gal.

#### Drying Time

Between 8 and 12 hours

#### Packaging Size

2 gal. Metal Combo Pail (A+B)

#### Shelf Life

24 months in original, unopened container

## ARIA WHITE CCI620

EPOXY COATING BASE COAT



### Epoxy Coating Base Coat

Pre-colored for white coats  
Special formulation for thicker coats  
Suitable for airplane hangars

#### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Cured Leveling Compounds, Radiant Heated Sub Floors, Drywall, Plaster, Stained Concretes (well bonded)

#### Approved Trowels/Spread Rate

XBL11 (1/8"x5/32"): up to 42 SF/gal.

#### Drying Time

Between 8 and 12 hours

#### Packaging Size

2 gal. Metal Combo Pail (A+B)

#### Shelf Life

24 months in original, unopened container

## QuikKote CCR630

WATER BASED EPOXY COATING



### Water Based Epoxy Coating

Economic Coat for Warehouse Flooring  
Can be tinted and/or flaked (except light colors)  
Full flake requires top coat  
Provides dust free and easy clean surface

#### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Cured Leveling Compounds, Radiant Heated Sub Floors, Drywall, Plaster, Stained Concretes (well bonded)

#### Approved Trowels/Spread Rate

3/8" Nap Roller: up to 200 SF/gal

#### Drying Time

Approx. 2 hours or until clear

#### Packaging Size

2-1/2 gal. Metal Combo Pail (A+B)

#### Shelf Life

24 months in original, unopened container

## ARIA RAPID UV CCO640

URETHANE (POLYASPARTIC) BASE COAT



### Urethane Coating Base Coat

Fast Drying  
Exceptional slip-resistance with sand broadcast.  
UV stable  
Can be tinted or flaked

#### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Cured Leveling Compounds, Radiant Heated Sub Floors, Drywall, Plaster, Stained Concretes (well bonded)

#### Approved Trowels/Spread Rate

3/8" Nap Roller up to 200 SF/gal.

#### Drying Time

Approx. 1 hour

#### Packaging Size

2 gal. Plastic Combo Pail (A+B)

#### Shelf Life

24 months in original, unopened container

## SUMMIT UV CCO650

URETHANE (POLYASPARTIC) TOP COAT



### Urethane Coating Top Coat

Fast Drying  
UV resistant  
Hot Tire Resistant  
Chemical Resistant

#### Approved Sub Floors

Concrete Slabs, Ceramic Tiles, Stone, Terrazzo, Cured Leveling Compounds, Radiant Heated Sub Floors, Drywall, Plaster, Stained Concretes (well bonded)

#### Approved Trowels/Spread Rate

3/8" Nap Roller: up to 240 SF/gal over rough surface  
3/8" Nap Roller: up to 360 SF/gal over smooth surface

#### Drying Time

Approx. 1 hour

#### Packaging Size

2 1/2 gal. Metal Combo Pail (A+B)

#### Shelf Life

24 months in original, unopened container